

NingBo SuRui Machinery Co., Itd

Add: Mingtang-ao Industrial park,Wuxiang town , Yinzhou District ,Ningbo China.--315042 Tel: +86-13857893619 Fax: +86-574-89007718 Web: www.threeplast-machinery.com / Email: daivd@threeplast-machinery.com



Characteristics

This Servo drive machine is designed For your Universal Processing applications this series of machinery is fast ,accurate and has Excellent Repeatability .This **THREEPLAST** injection molding machine can help you reach a maximum producibility on a wide range of materials . with a Bi-metal screw & Nitrided barrel . wear-resistant screw tip. High strength tie-bars and rigid platens . it all adds up to a unit ,that will stay the course ,giving consistently high quality and output with a wide range of materials and with the most complex of molds .



Machine Standard Features

Clamping Unit

Precise transducer for clamping /Ejector / Injection stroke control

Three platens / toggles made of highly-rigid ductile iron QT500-7A

Pre-drilled Robot mounting holes

Hydraulic gear-type mold height adjusting device

Mechanical / Electrical safety devices

Adjustment-free mechanical safety lock rod

Wear-resistant Manganese steel bands and supporting ,tracks for movable

Platen

Automatic central lubrication system

Multiple ejector function settings

Euromap Platen with T-Slots and mold mounting holes

Automatic mold height adjustment

Force ejector reset

Anti-crushing bump strips on the safety gate edges

Injection Unit

Parallel double-cylinder injection system

Low-speed high-torque hydraulic motor

Bi-metal screw and Nitrided barrel

Multi-stage PID nozzle and barrel temperature control

www.threeplast-machinery.com

Fully-closed heat band Cover

Nozzle safety cover

Cold start protection (oil heating function if the weather is Cold)

Linear guide for injection unit carriage

Automatic Material Purge

Selectable suck-back before or after plasticizing

Movable hopper (90T--320T)

Ceramic heater band

Back pressure control on PLC

Hydraulic System

Servo motor, pump system

Top branded hydraulic valve

Top branded hydraulic seal

Fast mold closing device

Built-in cooler

By pass Oil filter for Hydraulic oil

Hydraulic circuit design of mold opening stop (170T -- 500T)

Safety Retention device for exposed high-pressure hydraulic hose

Two set of core puller connector with valve

Mold water-cooling devices

www.threeplast-machinery.com

Electrical System

Forced barrel heating protection

Input / Output inspection

Automatic heat retaining and automatic heating setting

Ways of switching from injection to holding pressure:

time/ position / time + position

12" TFT color LCD

Memory space for up to 100 mold data sets ,USB Ports

Multiple operating languages

Color alarm light

2 blow Air

All transducers ,weak-current switches and reversing

solenoid valves enclosed by water-proof and rat-bite- proof corrugated pipes

Multi-level password security and key-locked operation Panel

Front and Rear safety gates with emergency stop protection

Back safety gates with stop protection (back door open stop the motor)

PDP interface

Statistical process control (SPC) interface

Reserved interfaces for air-blowing ,core pulling, ejector back protection devices, etc.

Two set of 3-phase power socket , AC 380V

One set of multi-function power socket ,AC 220V

SSR heating control

Euromap 67 / 12 Robot interface .

Others

Operation manual

Adjustable Leveling pad

A tool kit and precise filter element

Mold clamp

Spare parts (details as per sales contract)



Main Components

Description	Brand	Country of Original	
Servo Driver	INOVANCE	CHINA	
Servo Motor	PHASE	ITALY	
Servo Pump	SUMITOMO	JAPAN	
Connector	EATON	USA	
Valve	YUKEN	CHINA TAIWAN	
Controller computer	KEBA	AUSTRIA	
AC contactor	SCHNEIDER	FRANCE	
Stroke switch	SCHNEIDER	FRANCE	
Single-pole switch	SCHNEIDER	FRANCE	
Micro switch	SCHNEIDER	FRANCE	
Linear Transducer	OPKON	TURKEY	
Pressure Sensor	IFM	GERMANY	
Seal components	HALLITE	UK	
Hydraulic motor	DANDUN	CHINA	
Lubrication system	RUNZHOU	CHINA	

Machine Specifications

TH130						
Injection Unit		A	В	C		
Screw Diameter	In	1.5	1.65	1.77		
	mm	38	42	45		
Screw L/D ration	L/D	22	20	18.5		
Shot volume	in3	11.9	14.52	16.96		
	Cm3	195	238	274		
Shot weight (PS)	g	178	217	249		
	OZ	6.28	7.65	8.78		
Injection Pressure	psi	30160	24795	21460		
	Мра	208	171	148		
Max screw speed	rpm		200	-		
Clamping Unit						
Clamping Force	KN / T	1300 / 130				
	U.S.ton	143				
Opening stroke	In	14.96				
	mm	380				
Tie-bars distance	In	16.41 X 16.41				
	mm	417 X 417				
Max.mold height	In	18.11				
	mm	460				
Min.mold height	In	7.08				
	mm	180	180			
Ejector Stroke	In	4.72				
	mm	120				
Ejector force	KN	46	46			
	U.S. ton	5.06				
General						
Pump power	Kw	15				
	HP	20.1				
Heating capacity	Kw	7.4				
	HP	9.92				
Oil tank Capacity	Litre	220				
Machine Dimensions	In	181.10 X 53.15 X 82.68				
	m	4.60 X 1.35 X 2.10				
Machine weight	Kg	4300				
	Lbs	9460				



Price for TH130

Molde	Tie-bars Distance	Shot weight (PS)	Clamping	Price
		By standard B screw	Force	USD
		42 mm		
TH130	417 X 417 mm	217 g	130 T	22300
	16.41 X 16.41 Inch	7.65 oz		
	0			
Net price				22300

By: David Ye. Date: 2021/10/28

Note:

- 1. Price condition : FOB NINGBO
- 2. Payment Items: 30% TT in advance , 70 % TT before Delivery
- 3. Delivery Term: By sea
- 4. Loading Port: NingBo Port
- 5. Packing Method: Standard Export Package
- 6. Delivery time: Within 40 days after received advance payment.
- 7. This offer is valid for 90 days only .

Warranty

1. Machine Hydraulic part & Mechanical part warranty Period of two years . (include : casting ,tie-bars ,injection ,clamping & ejector manifolds ,toggle links and carriage guide rod , Hydraulic hoses , position sensor , bushings, toggle pins, Hydraulic valves, proportional valve, Hydraulic screw motor and hydraulic pump)

- 2. Screw & Barrel warranty Period of 12 months . (new plastic material)
- 3. Electronic components warranty Period of two years.

4. Warranty does not include any improper use by customer operation and the loss cause by wrong operation .

5. Warranty is limited to the replacement of damaged parts , not including the Tax on customers . delivery charge .consumption and lost .

6. Warranty does not include any profit loss ,loss of production or the resulting any loss.





www.threeplast-machinery.com

CE & EC type Examination Certificate



Factory Glance



www.threeplast-machinery.com



Customers





www.threeplast-machinery.com

Shipping



We Also Provide Mould and Auxiliary Equipment :



Auto loader

Mould

Hopper dryer



Mixer





Crusher/Granulator Chiller
And Others Customer needs





Mould Temperature controller

www.threeplast-machinery.com