

Da:

Evol Automation s.r.l.s.

 via Manfredonia, 15
 71121 Foggia (158)
 Italia

 Telefono: 08811781538/3351342929 - Fax:
 08811781538
 Email: evolautomation@libero.it

A:

Alfred jäeger

 Siemensstraße 8
 D-61239 Ober-Mörlen
 Germania

Importo in valuta Euro

Descrizione	IVA	P.U.(netto)	Qtà	Totale Netto
Vendor SKU 10404082 - HF-Motor Spindle Z62-H360.02 S19W2/2 with 4 Pcs. ceramic hybrid precision ball bearings lubricated for life. - power output Pmax/5s : 3.2 kW S6-60% : 2,1 kW S1-100% : 1,8 kW - rotation : max. 60.000 rpm - housing diameter : 61,90 mm - tool change : pneumatic HSK-E 25 - toolholder monitoring : inductive relay - 2 position : clamped, eject - clamping range : up to 8 mm - cooling : liquid cooled - speed transmitter - motor protection : PTC - sealing air - Taper cleaning - coupler plug : Y-Tec metal 9-pole (motor phases, PE, PTC, FP) 12-pole (tool holder monitoring) - weight : 6,2 kg incl. HSK-protection cap and cleaning-cone	0%	4 500,00	1	4 500,00
Vendor SKU 41320006-001 - connection lead GB9-12Y/- Sper.,Küh.,Pne Operation connection line - EMV shield motorcable - internal control-line separate shield - 9-pole socket (power section) -12-pole socket (control cable) - oil constant as VDE 0472 § 804 - cooling water hose advance and return - sealing air-hose - compressed air-hose pneumatic cylinder forward and back - compressed air-hose taper cleaning	0%	159,21	1	159,21
Vendor SKU 41320006-002 - surcharge Connection lead per running me surcharge BAL 0,75-8-8-6-6-6 per running meter 5 Meter 31,20 156,00 1x motor cable 4x0,752 + 5x0,252 mm 1x control cable 12x0,142 2x hose, black Ø8/5,5 1x hose, blue Ø6/4 2x hose, red Ø6/4 1xhose green Ø6/4 1x cable protective tube , NW 32	0%	31,00	5	155,00

